ELECTRA 1038 Be

Product specification sheet



Advanced γ Structure

Massive structure up to 2" (50mm)

thick MDF

No diffraction effect nor vibration

OPC (Optimum Phase Crossover)
Perfect staging
Focal binding posts offering high
torque and excellent contact

Front laminar port No noise, no distortion No dynamic compression







- Made in France loudspeakers and drivers
- ◆ Very high power handling

Side panel standard finishes (body in Slate Grey)*



 $\ensuremath{^{*}}\xspace$ On demand finishes for side panels: Macassar and Zebrano

Туре	3-way vented floor standing speaker
Drivers	Three 7" (18cm) "W" woofers 6 ^{1/2} " (16.5cm) "W" midrange 1 ^{1/4} " (27mm) pure Beryllium IAL inverted dome tweeter
Frequency response (+/-3dB)	33Hz - 40kHz
Low frequency point (-6dB)	26Hz
Sensitivity (2.83V/1m)	93dB
Nominal impedance	8Ω
Minimum impedance	3.3Ω
Crossover frequency	230Hz / 2200Hz
Recommended amplifier power	40 - 400W
Dimensions (HxWxD)	49 ^{3/16} x11 ^{15/16} x15 ^{3/4} " (1 250x303x400mm)
Net weight	112.2lb (51kg)

As the whole Electra Be 2 line, the 1038 Be benefits from new components and settings. The awesome strength of the three 7" (18cm) woofers, endless power, is now added to the new qualities gained in terms of sound image and definition. A true weapon of mass seduction.



