

CS-16C II

6.5" In-Ceiling Speaker



GOOD SOUND FOR ANY ROOM

Using the same design principles of our premium architectural and box speaker lines, the all new Klipsch Contractor series delivers true Klipsch power and performance to any budget. With a 6.5" Polymer woofer and a 1" Polymer Dome tweeter the CS-16C II brings dynamic, powerful, detailed Klipsch sound to your distributed audio, home theater, or 2-channel system.

PATENT-PENDING SKYHOOK™ TOOL-FREE INSTALLATION SYSTEM

The exclusive installation system engages the dog legs automatically when the speaker is inserted into the cutout hole with a preset clamping force, eliminating the possibility of overtorquing. This fast, easy installation system reduces install time by up to 75%.

ALL NEW, BEZEL-FREE MAGNETIC GRILLE

A completely redesigned powdercoated magnetic steel grille eliminates the bezel for seamless, pristine integration into the living space.

SPECIFICATIONS

FREQUENCY RANGE	65Hz - 20kHz +/- 3dB
HIGH FREQUENCY DRIVER	1" (2.54cm) Polymer Dome Tweeter
LOW FREQUENCY DRIVER	6.5" (16.51cm) Polymer Woofer
SENSITIVITY	91 dB @ 2.83V / 1m
POWER HANDLING	40W RMS / 160W Peak
IMPEDANCE	8 Ohm Compatible
ENCLOSURE MATERIAL/TYPE	ABS/Infinite Baffle
FINISH	Black Baffle/Frame, White Paintable Grille
PRODUCT DIMENSIONS	9.2" W x 9.2" H x 4.5" D (23.3cm H x 23.3cm W x 11.3cm D)
MOUNTING DEPTH	4.34" (11.03cm)
CUTOUT DIMENSIONS	8.3" (21.1cm)
PRODUCT WEIGHT	7 lbs (3.18kg)
INCLUDED IN BOX	Flat Paintable Magnetic Grille
INSTALL KIT	IK-650-C II (Sold Separately)
FIRE RATED ENCLOSURE	ME-650-C (Sold Separately)
BUILT FROM	2017